

▲ Indications, Safety, and Warnings

HEALTHCARE PROFESSIONALS

Rebar Reinforced Micro Catheter

Peripheral Embolization



OVERVIEW

The Rebar™ reinforced micro catheter is a single-lumen catheter introduced via a steerable guidewire into the vasculature. Its stainless-steel construction, high kink resistance, and hydrophilic coating help navigate tortuous anatomy and deploy therapeutic agents or contrast media with ease.

INDICATIONS

The Rebar reinforced micro catheter is intended for the controlled selective infusion of physician-specified therapeutic agents or contrast media into the vasculature of the peripheral and neuro anatomy.

PRODUCT DETAILS

The catheter's semi-rigid proximal shaft transitions into a flexible distal shaft, facilitating advancement into the anatomy. A standard luer adapter at the proximal end enables ready attachment of accessories.*

PUSHABILITY AND VISIBILITY*

- Continuous stainless-steel construction provides added reinforcement
- High resistance to kinking when maneuvering around tight bends
- Distal radiopaque marker aids fluoroscopic visualization

SMOOTH DELIVERY*

- Lubricious hydrophilic outer coating helps navigate tortuous vessels and reduce resistance
- PTFE inner liner eases the passage and deployment of embolic devices and agents
- DMSO compatible

SUPERSELECTIVITY*

 Steam-shapeable catheter tip through the use of a mandrel enables treatment of super selective vessels

MANUALS AND TECHNICAL GUIDES

Instructions for Use

Find this technical manual in the product labeling supplied with each device or call Medtronic at +1 763-526-7890.

MODEL SPECIFICATIONS

REBAR REINFORCED MICRO CATHETER**



	Product Code	Proximal OD/ Distal OD (F)	Distal ID (inch)	Total Length (cm)	Usable Length (cm)
Rebar-18	105-5081-130	2.7/2.4	0.021	137	130
Rebar-18	105-5083-153	2.7/2.4	0.021	160	153
Rebar-27	105-5082-145	2.8/2.8	0.027	150	145

RELATED PAGES

Peripheral Embolization Products

REQUEST MORE INFORMATION

CONTACT US

^{*}Data on file at Medtronic

^{**}Allowable dynamic pressure 700 PSI